



# HOMEE COMPATIBILITY OVERVIEW

Status 08 | 2021

# homee compatibility overview

Status 08 | 2021








**EXPAND YOUR POSSIBILITIES.** With the Hörmann homee Brain Smart Home control centre, you can open and close your Hörmann doors and gates even more conveniently.

Door operators							
	SupraMatic E/P 4	SupraMatic E/P 3		SupraMatic HT3	ProMatic 4	ProMatic 3	RollMatic 2
For product	Garage door	Garage door		Garage door	Garage door	Garage door	Garage door
For series	4	3	3	3	4	3	4
From year of manufacture	2019	2012			2019	2012	2022
From index		Bi	Ci			Bi	
	<b>homeegramm</b>						
<b>Functions</b>							
Open / close impulse			●	●			●
Open		●	●	○	○	●	●
Close		●	●	○	○	●	●
Partial opening		●	●	●	○	●	●
Light on / off		●	●	●	○	●	●
Ventilation		●				●	●
	<b>Display</b>						
<b>Feedback</b>							
Open	●	●	●	●	○	●	●
Closed	●	●	●	●	○	●	●
Partially open	●	●	●	●	○	●	●
Ventilation	●	●				●	●








● = As standard  
 ○ = Optionally with receiver ESE BS  
 \* In conjunction with a multi-function / travel limit circuit board

# homee compatibility overview

Status 08 | 2021

Door operators	RotaMatic / P / PL / Akku-Solar		VersaMatic / P / Akku-Solar		LineaMatic / P / Akku-Solar		LineaMatic H	
	Hinged gate		Hinged gate		Sliding gate		Sliding gate	
For product	Hinged gate		Hinged gate		Sliding gate		Sliding gate	
For series	2	1	1		2	1	1	
From year of manufacture	2017	2013	2017		2017	2012	2017	
From index	A	G			A	E	A	
<b>homeegramm</b>								
<b>Functions</b>								
Open / close impulse			●	●	●	●	●	○
Open		●	●	●	●	●	●	○
Close		●	●	●	●	●	●	○
Partial opening			●	●	●	●	●	○
Light on / off			●		●	●		
<b>Display</b>								
<b>Feedback</b>								
Open		●	●	●	●	●	●	○
Closed		●	●	●	●	●	●	○
Partially open		●	●	●	●	●	●	○














● = As standard  
○ = Optionally with receiver ESE BS  
\* In conjunction with a multi-function / travel limit circuit board

Door operators	WA 300 R S4	WA 300 S4	HET-E2 BS			
	Industrial rolling shutter	Industrial sectional door	Receiver for operator WA 400			
For product	Industrial rolling shutter	Industrial sectional door	Receiver for operator WA 400			
For series	1	1	1			
From year of manufacture	2014	2014				
From index	C	D				
<b>homeegramm</b>						
<b>Functions</b>						
Open / close impulse				○	○	
Open		●		○	○	●*
Close		●		○	○	●*
Partial opening				○	○	
Light on / off						
<b>Display</b>						
<b>Feedback</b>						
Open		●		○	○	●*
Closed		●		○	○	●*
Partially open		●		○	○	
















● = As standard  
○ = Optionally with receiver ESE BS  
\* In conjunction with a multi-function / travel limit circuit board

# homee compatibility overview

Status 08 | 2021

Door and lock operators			
For product	Residential internal doors	Residential internal / function doors	Aluminium entrance doors
From year of manufacture	2016	2017	
From software index			
	<b>homeegramm</b>		
<b>Functions</b>			
Open / close impulse		•	
Open		•	•
Permanent opening on / off			•
Unlocking		•	•
Unlocking (temporary)			•
Locking		•	•
Light on / off		•	
Automatic on / off		•	
	<b>Display</b>		
<b>Feedback</b>			
Open	•	•	•
Closed	•	•	
Partially open	•	•	
Permanent opening on / off	•		•
Unlocked	•	•	•
Locked	•	•	•
Start delay on / off	•	•	
Automatic timer on / off	•	•	
Battery status	•	•	

● = As standard  
○ = with latch switching contact

Receivers						
For product	Electrical devices	Electrical devices	Socket	Socket / operators of other makers	Electrical devices	Automatic bollards
From year of manufacture	2016	2012	2016	2016	2016	2018
From software index	A					
	<b>homeegramm</b>					
<b>Functions</b>						
On / off impulse		•	•	•	•	
Switch on for 0.5 s		•	•	•		
Switch on for 3 – 180 s			•			
Switch on		•		•	•	
Switch off		•		•	•	
Lift / lower impulse						•
Lowering						•
	<b>Display</b>					
<b>Feedback</b>						
Switched on	•	•	•	•	•	
Switched off	•	•	•	•	•	
Lowered	•					•
Raised	•					•
Partially lowered	•					•

● = As standard  
\* Signal kit required