FITTING INSTRUCTION

Part Numbers APG40/70/130/140/150 Arcadian Replacement Rollers and Spindles for Catnic/Garador Canopy Doors.

<u>WARNING</u> As spring tension is on the door at all times great care must be taken.

All work is undertaken from within the garage so ensure that all tools required are at hand. You may require assistance with step (1)

- 1 Slide the plastic spring cover along and remove. Using a piece of cloth to protect your hand, grasp the cable and pull it towards the centre of the door until the spring is engaged in its socket (rear of spring bracket has a lug on it and the spring box has a location slot for the plug). This will remove the tension from the cable.
- 2 Remove the screw at the base of the side jamb channel and the screw holding the bracket half way up (if fitted). This allows removal of the cable from the roller and spindle.
- 3 Remove the old roller and spindle and replace with the new one in the same manner. Ensure that the cable is located in the 'G' bracket on the new spindle.
- 4 Replace the screws in the side jamb channel.
- 5 Using a piece of cloth to protect your hand take up the slack on the cable, check carefully that the cable is running correctly in the pulley wheels, then pull the cable to release the spring from its holding bracket and gently allow the cable to return to its original position.

Repeat steps 1 to 5 to replace the roller and spindle on the other side.

NOTE: If there is insufficient room between the brickwork and the spindles to remove them, remove the bottom weather strips and ease the bottom of the door into the garage. This will allow sufficient room to remove and replace the rollers and spindles

ALL WORK IS UNDERTAKEN AT THE OWNERS RISK